




The TBJ COTS-Plus series, based on the CWR11 form factor, is a high reliability series encompassing the current range of EIA Low ESR ratings. These ratings are available with Weibull grading (B and C), surge current testing (A, B, C) per MIL-PRF-55365 Rev. G, and optional Group A from MIL-PRF-55365.

For Space Level applications, AVX SRC9000 qualification is recommended. Please refer to the TBJ COTS-Plus SRC9000 Datasheet for part number availability.

There are five termination finishes available: solder plated, fused solder plated, hot solder dipped, 100% Tin and gold plated (these correspond to "H", "K", "C", "7" and "B" termination, respectively). The molding compound has been selected to meet the requirements of UL94V-0 (Flame Retardancy) and outgassing requirements of ASTM E-595.

For moisture sensitivity levels please refer to the High Reliability Tantalum MSL section located in the back of the High Reliability Tantalum Catalog.

CASE DIMENSIONS: millimeters (inches)




Code	EIA Code	EIA Metric	L±0.20 (0.008)	W+0.20 (0.008) -0.10 (0.004)	H+0.20 (0.008) -0.10 (0.004)	W ₁ ±0.20 (0.008)	A+0.30 (0.012) -0.20 (0.008)	S Min.
A	1206	3216-18	3.20 (0.126)	1.60 (0.063)	1.60 (0.063)	1.20 (0.047)	0.80 (0.031)	1.10 (0.043)
B	1210	3528-21	3.50 (0.138)	2.80 (0.110)	1.90 (0.075)	2.20 (0.087)	0.80 (0.031)	1.40 (0.055)
C	2312	6032-28	6.00 (0.236)	3.20 (0.126)	2.60 (0.102)	2.20 (0.087)	1.30 (0.051)	2.90 (0.114)
D	2917	7343-31	7.30 (0.287)	4.30 (0.169)	2.90 (0.114)	2.40 (0.094)	1.30 (0.051)	4.40 (0.173)
E	2917	7343-43	7.30 (0.287)	4.30 (0.169)	4.10 (0.162)	2.40 (0.094)	1.30 (0.051)	4.40 (0.173)
V	2924	7361-38	7.30 (0.287)	6.10 (0.240)	3.55 (0.140)	3.10 (0.120)	1.30 (0.051)	4.40 (0.173)

W₁ dimension applies to the termination width for A dimensional area only.

MARKING

A, B, C, D, E, V CASE



HOW TO ORDER

AVX PART NUMBER:

TBJ	D	227	*	035	C	B	S	Z	0	0	00
Type	Case Size	Capacitance Code	Capacitance Tolerance	Voltage Code	ESR	Packaging	Inspection Level	Reliability Grade	Qualification Level	Termination Finish	Surge Test Option
		pF code: 1st two digits represent significant figures 3rd digit represents multiplier (number of zeros to follow)	K = ±10% M = ±20%	002 = 2Vdc 004 = 4Vdc 006 = 6.3Vdc 010 = 10Vdc 016 = 16Vdc 020 = 20Vdc 025 = 25Vdc 035 = 35Vdc 050 = 50Vdc	C = Std ESR L = Low ESR	B = Bulk R = 7" T&R S = 13" T&R W = Waffle	S = Std. Conformance L = Group A	Weibull: B = 0.1%/1000 hrs. 90% conf. C = 0.01%/1000 hrs. 90% conf. Z = Non-ER	0 = N/A	H = Solder Plated 0 = Fused Solder Plated 8 = Hot Solder Dipped 9 = Gold Plated 7 = Matte Sn	00 = None 23 = 10 Cycles, +25°C 24 = 10 Cycles, -55°C & +85°C 45 = 10 cycles, -55°C & +85°C before Weibull



For RoHS compliant products, please select correct termination style.

TECHNICAL SPECIFICATIONS

Technical Data:	Unless otherwise specified, all technical data relate to an ambient temperature of 25°C									
Capacitance Range:	0.10 µF to 1500 µF									
Capacitance Tolerance:	±10%; ±20%									
Rated Voltage (V _R)	≤ 85°C:	2	4	6	10	16	20	25	35	50
Category Voltage (V _C)	≤ 125°C:	1.4	2.7	4	7	10	13	17	23	33
Surge Voltage (V _S)	≤ 85°C:	2.6	5.2	8	13	20	26	32	46	65
Surge Voltage (V _S)	≤ 125°C:	1.7	3.4	5	8	13	16	20	28	40
Temperature Range:	-55°C to +125°C									

CAPACITANCE AND RATED VOLTAGE, V_R (VOLTAGE CODE) RANGE (LETTER DENOTES CASE SIZE)

Capacitance		Rated Voltage DC (V_R) to 85°C									
μF	Code	2V	4V	6V	10V	15V	16V	20V	25V	35V	50V
0.10	104									A(24000)	A(22000)
0.15	154									A(21000)	A(9000, 21000) B(17000)
0.22	224									A(6000, 18000)	A(7000, 18000) B(14000)
0.33	334									A(6000, 15000)	B(12000)
0.47	474							A(14000)	A(7000, 14000)	A(6000, 12000) B(4000, 10000)	C(8000)
0.68	684					A(12000)	A(12000)	A(12000)	A(6000, 10000) B(7500)	A(6000, 8000) B(8000)	A(7900) C(7000)
1.0	105				A(10000)	A(10000)	A(10000)	A(3000, 10000)	A(8000) B(6500)	A(3000, 7500) B(2000, 6500)	C(2500, 6000)
1.5	155			A(8000)	A(8000)	A(8000)		A(6500) B(6000)	A(3000, 7500) B(1800, 6500)	A(7500) B(2500, 5200) C(4500)	C(1500, 5000) D(4000)
2.2	225		A(8000)	A(8000)	A(1800, 8000)	B(5500)	A(1800, 5500) B(5000)	A(3000, 5300) B(5000)	A(7000) B(900, 4500) C(3500)	A(1500, 4500) B(2000, 4200) C(1000, 3500)	D(1200, 2500)
3.3	335			A(8000)	B(5500)	B(5000)	A(3500, 5000) B(4500)	A(2500) B(1300, 4000)	A(2800) B(750, 3500) C(3500)	B(1000, 3500) C(700, 2500)	D(800, 2000)
4.7	475		A(8000)	B(5500)	A(1400, 5000) B(4500)	B(4000)	A(2000, 4000) B(800, 3100)	A(1800, 4000) B(750, 3000) C(3000)	B(1500, 2300) C(2500)	B(700, 3100) C(600, 2200) D(500, 1500)	D(300, 1500)
6.8	685		B(5500)	A(1800, 5000) B(4500)	A(1800, 4000) B(3500)		A(1500, 2500) B(60, 2500)	A(1000) B(600, 2500) C(700, 2400)	B(700, 2800) C(500, 2000) D(1400)	C(350, 1800) D(500, 1300)	D(500, 1000)
10	106		B(4000)	A(1500, 4000) B(3500)	A(1800, 3000) B(2500)	C(2500)	A(1000, 3000) B(500, 2800) C(500, 2500)	B(1000, 2100) C(500, 1900)	C(500, 1800) D(1200)	C(600, 1600) D(300, 1000) E(200, 250)	E(400, 500) V(650)
15	156		B(3500)	A(1500, 3500) B(3500) C(3000)	A(1000, 3200) B(450, 2800) C(2500)		B(800, 2500) C(1800)	B(500, 2000) C(400, 1700) D(1100)	C(220, 300) D(300, 1000)	C(350, 1400) D(300, 900)	D(600) E(250, 600)
22	226			A(500, 3000) B(375, 2500) C(2200)	B(700, 2400) C(300, 1000)	D(1100)	B(600, 2300) C(375, 1600) D(1100)	B(400, 600) C(150, 1600) D(200, 900)	C(275, 1400) D(200, 900)	D(400, 900) E(300, 900)	V(390, 600)
33	336		A(3000) C(2200)	A(600) B(600, 2200)	A(700, 1700) B(250, 1800) C(150, 1600) D(1100)	D(900)	B(350) C(300, 1500) D(200, 900)	C(300, 1500) D(100, 900)	D(100, 900) E(300, 900)	D(300, 900) E(100, 250) V(200)	
47	476		A(500)	A(800) B(250, 350) C(300, 1600) D(1100)	B(250, 350) C(200, 1200) D(100, 900)		C(350, 1500) D(150, 900)	D(100, 200) E(70, 250)	D(250, 900) E(80, 100)	E(200, 250) V(200, 400)	
68	686		D(1100)	B(250, 1800) C(150, 1600) D(900)	B(600) C(80, 1200) D(100, 900)		C(125, 200) D(70, 900)	D(70, 900) E(150, 900)	E(125, 200) V(95)	V(150, 200)	
100	107		A(1400) B(200, 1600)	B(250, 400) C(150, 900) D(900)	B(400) C(200, 1200) D(100, 900) E(125)		D(125, 900) E(100, 900)	D(85, 100) E(100, 150) V(85, 200)	V(100)		
150	157	B(150)	B(250) C(70, 80)	C(50, 90) D(50, 900)	D(150, 900) E(100)		D(150, 900) E(100, 300) V(45, 75)	E(300) V(80)			
220	227	B(150, 200) D(45)	D(40, 900)	C(70, 1200) D(100, 900) E(100)	D(150, 900) E(100, 900)		E(100, 150) V(75, 150)				
330	337		C(100) D(35, 45)	D(45, 50) E(100, 900) V(100)	D(150, 900) E(60, 900) V(60, 100)						
470	477	D(35)	D(45, 100) E(35)	D(45, 60) E(50, 900) V(55, 100)	E(50, 900) V(60, 100)						
680	687	D(35, 50) E(35, 50)	D(45, 60) E(40, 60)	E(45, 60) V(35, 40)							
1000	108	E(30, 40)	E(60) V(25, 35)	V(40, 50)							
1500	158	D(100) E(50) V(30, 40)	E(50, 75) V(50, 75)								

Available Ratings: ESR limits quoted in brackets (mOhms)

Not recommended for new designs, higher voltage or smaller case size substitution are offered.

Notes: Voltage ratings are minimum values. AVX reserves the right to supply higher ratings in the same case size, to the same reliability standards.

TBJ Series

COTS-Plus



RATING & PART NUMBER REFERENCE		Parametric Specifications by Rating per MIL-PRF-55365/4				Typical RMS Ripple Data by Rating								
Cap @ 120Hz	DC Rated Voltage @ +85°C	ESR @ 100kHz	DCL max		DF Max + (85/125)°C	Power Dissipation	25°C		85°C		125°C			
			+25°C (μA)	+85°C (μA)			Ripple Current (100kHz)	Ripple Current (100kHz)	Ripple Current (100kHz)	Ripple Current (100kHz)	Ripple Voltage (100kHz)	Ripple Voltage (100kHz)	Ripple Voltage (100kHz)	Ripple Voltage (100kHz)
Case	V	Ohms @ +25°C	(μA)	(μA)	(%)	W	A	A	A	V	V	V		
TBJ157*002L1#00++	B	150	2	0.15	3	60	30	0.753	0.677	0.301	0.113	0.102	0.045	
TBJ227*002C1#00++	B	220	2	0.2	4.4	88	44	0.682	0.587	0.261	0.130	0.117	0.052	
TBJ227*002L1#00++	B	220	2	0.15	4.4	88	44	0.085	0.677	0.301	0.113	0.102	0.045	
TBJ227*002L1#00++	D	220	2	0.045	4.4	88	44	0.150	1.826	1.643	0.730	0.082	0.074	0.033
TBJD47*002L1#00++	D	470	2	0.035	9.4	94	188	0.150	2.070	1.863	0.828	0.072	0.065	0.029
TBJD87*002C1#00++	D	680	2	0.05	13.6	136	272	0.150	1.732	1.559	0.693	0.087	0.078	0.035
TBJD87*002L1#00++	D	680	2	0.035	13.6	136	272	0.150	2.070	1.863	0.828	0.072	0.065	0.029
TBJE687*002C1#00++	E	680	2	0.05	13.6	136	272	0.165	1.817	1.635	0.727	0.091	0.082	0.036
TBJE687*002L1#00++	E	680	2	0.035	13.6	136	272	0.165	2.171	1.954	0.868	0.076	0.068	0.030
TBJE108*002C1#00++	E	1000	2	0.04	20	200	400	0.165	2.031	1.828	0.812	0.081	0.073	0.030
TBJE108*002L1#00++	E	1000	2	0.03	20	200	400	0.165	2.345	2.111	0.938	0.070	0.063	0.028
TBJD158*002L1#00++	D	1500	2	0.1	30	300	600	0.150	1.225	1.102	0.490	0.122	0.110	0.049
TBJE158*002L1#00++	E	1500	2	0.05	30	300	600	0.165	1.817	1.635	0.727	0.091	0.082	0.036
TBM158*002C1#00++	V	1500	2	0.04	30	300	600	0.250	2.500	2.250	1.000	0.100	0.090	0.040
TBM158*002L1#00++	V	1500	2	0.03	30	300	600	0.250	2.887	2.598	1.155	0.087	0.078	0.035
TBJA25*004C1#00++	A	2.2	4	8	0.088	1.76	6	0.075	0.097	0.087	0.039	0.075	0.069	0.310
TBJA475*004C1#00++	A	4.7	4	8	0.188	3.76	6	0.075	0.097	0.087	0.039	0.075	0.069	0.310
TBJB685*004C1#00++	B	6.8	4	5.5	0.272	2.72	5.44	0.085	0.124	0.112	0.050	0.084	0.615	0.273
TBJB106*004C1#00++	B	10	4	4	0.4	4	8	0.085	0.146	0.131	0.058	0.083	0.525	0.233
TBJB156*004C1#00++	B	15	4	3.5	0.6	6	12	0.085	0.156	0.140	0.062	0.082	0.545	0.491
TBJA336*004C1#00++	A	33	4	3	1.32	13.2	26.4	0.075	0.124	0.112	0.050	0.084	0.615	0.273
TBJC336*004C1#00++	C	33	4	2.2	1.32	13.2	26.4	0.110	0.224	0.201	0.089	0.130	0.117	0.052
TBJA476*004L1#00++	A	47	4	0.5	1.88	18.8	37.6	0.075	0.387	0.349	0.155	0.194	0.174	0.077
TBJC686*004C1#00++	C	68	4	1.6	2.72	27.2	54.4	0.110	0.262	0.236	0.105	0.148	0.378	0.168
TBJD686*004C1#00++	D	68	4	1.1	2.72	27.2	54.4	0.150	0.369	0.332	0.148	0.406	0.366	0.162
TBJA107*004C1#00++	A	100	4	1.4	4	40	80	0.075	0.231	0.208	0.093	0.324	0.292	0.130
TBJB107*004C1#00++	B	100	4	1.6	4	40	80	0.085	0.230	0.207	0.093	0.324	0.292	0.130
TBJB107*004L1#00++	B	100	4	0.2	4	40	80	0.085	0.632	0.587	0.261	0.130	0.117	0.052
TBJB157*004L1#00++	B	150	4	0.25	6	60	120	0.085	0.583	0.525	0.233	0.146	0.131	0.058
TBJC157*004C1#00++	C	150	4	0.08	6	60	120	0.110	1.173	1.056	0.469	0.094	0.084	0.038
TBJC157*004L1#00++	C	150	4	0.07	6	60	120	0.110	1.254	1.128	0.501	0.088	0.079	0.035
TBJD227*004C1#00++	D	220	4	0.9	8.8	88	176	0.150	0.408	0.367	0.163	0.367	0.331	0.147
TBJD227*004L1#00++	D	220	4	0.04	8.8	88	176	0.150	1.936	1.743	0.775	0.077	0.070	0.031
TBJC337*004L1#00++	C	330	4	0.1	13.2	132	264	0.110	1.049	0.944	0.420	0.105	0.094	0.042
TBJD337*004C1#00++	D	330	4	0.045	13.2	132	264	0.150	1.826	1.643	0.730	0.082	0.074	0.033
TBJD337*004L1#00++	D	330	4	0.035	13.2	132	264	0.150	2.070	1.863	0.828	0.072	0.065	0.029
TBJD477*004C1#00++	D	470	4	0.1	18.8	188	376	0.150	1.225	1.102	0.490	0.122	0.110	0.049
TBJD477*004L1#00++	D	470	4	0.045	18.8	188	376	0.150	1.826	1.643	0.730	0.082	0.074	0.033
TBJE477*004L1#00++	E	470	4	0.035	18.8	188	376	0.165	2.171	1.954	0.868	0.076	0.068	0.030
TBJD687*004C1#00++	D	680	4	0.06	27.2	272	544	0.150	1.581	1.423	0.632	0.095	0.085	0.038
TBJD687*004L1#00++	D	680	4	0.045	27.2	272	544	0.150	1.826	1.643	0.730	0.082	0.074	0.033
TBJE687*004C1#00++	E	680	4	0.06	27.2	272	544	0.165	1.658	1.492	0.663	0.099	0.090	0.040
TBJE687*004L1#00++	E	680	4	0.04	27.2	272	544	0.165	2.031	1.828	0.812	0.081	0.073	0.032
TBJE108*004L1#00++	E	1000	4	0.06	40	400	800	0.165	1.658	1.492	0.663	0.099	0.090	0.040
TBM108*004C1#00++	V	1000	4	0.035	40	400	800	0.250	2.673	2.405	1.089	0.094	0.084	0.037
TBM108*004L1#00++	V	1000	4	0.025	40	400	800	0.250	3.162	2.846	1.265	0.079	0.071	0.032
TBJE158*004C1#00++	E	1500	4	0.075	60	600	1200	0.165	1.483	1.335	0.593	0.111	0.100	0.044
TBJE158*004L1#00++	E	1500	4	0.05	60	600	1200	0.165	1.817	1.635	0.727	0.091	0.082	0.036
TBM158*004C1#00++	V	1500	4	0.075	60	600	1200	0.250	1.826	1.643	0.730	0.137	0.123	0.055
TBM158*004L1#00++	V	1500	4	0.05	60	600	1200	0.250	2.236	2.012	0.894	0.112	0.101	0.045
TBJA155*006C1#00++	A	1.5	6	8	0.09	0.9	1.08	0.075	0.097	0.087	0.039	0.075	0.069	0.310
TBJA25*006C1#00++	A	2.2	6	8	0.198	1.98	1.32	0.075	0.097	0.087	0.039	0.075	0.069	0.310
TBJA335*006C1#00++	A	3.3	6	8	0.198	1.98	1.32	0.075	0.097	0.087	0.039	0.075	0.069	0.310
TBJA475*006C1#00++	A	4.7	6	5.5	0.282	2.82	3.384	0.085	0.124	0.112	0.050	0.084	0.615	0.273
TBJA685*006C1#00++	B	6.8	6	5	0.408	4.08	8.16	0.075	0.122	0.110	0.049	0.612	0.551	0.245
TBJA685*006L1#00++	A	6.8	6	1.8	0.408	4.08	8.16	0.075	0.204	0.184	0.082	0.367	0.331	0.147

All technical data relates to an ambient temperature of +25°C. Capacitance and DF are measured at 120Hz, 0.5V RMS with a maximum DC bias of 2.2 volts. DCL is measured at rated voltage after 5 minutes.

NOTE: AVX reserves the right to supply a higher voltage rating or tighter tolerance part in the same case size, to the same reliability standards.



TBJ Series

COTS-Plus



RATING & PART NUMBER REFERENCE		Parametric Specifications by Rating per MIL-PRF-55365/4						Typical RMS Ripple Data by Rating						
		Cap @ 25°C	DC Rated Voltage	ESR @ 100kHz	DCL max	DF Max	Power Dissipation	25°C	85°C	125°C	25°C	85°C	125°C	
AVX COTS-Plus P/N	Case	µF	V	Ohms	µA	(%)	(%)	W	A	A	A	V	V	V
		@ +25°C	@ +85°C	@ +25°C	+125°C	+25°C	+85°C		(100kHz)	(100kHz)	(100kHz)	(100kHz)	(100kHz)	(100kHz)
TBJB685*006C1#00++	B	6.8	6	4.5	4.08	4.896	6	0.085	0.137	0.124	0.055	0.618	0.557	0.247
TBJA106*006C1#00++	A	10	6	4	6	12	6	0.075	0.137	0.123	0.055	0.548	0.493	0.219
TBJA106*006L1#00++	A	10	6	1.5	0.6	6	6	0.075	0.137	0.123	0.055	0.548	0.493	0.219
TBJA106*006C1#00++	B	10	6	3.5	0.6	6	6	0.085	0.156	0.140	0.062	0.545	0.491	0.218
TBJA156*006C1#00++	A	15	6	3.5	0.9	18	6	0.075	0.146	0.132	0.059	0.512	0.461	0.205
TBJA156*006L1#00++	A	15	6	1.5	0.9	18	6	0.075	0.224	0.201	0.089	0.335	0.302	0.134
TBJB156*006C1#00++	B	15	6	3.5	0.225	2.25	6	0.085	0.156	0.140	0.062	0.545	0.491	0.218
TBJC156*006C1#00++	C	15	6	3	0.9	9	6	0.110	0.191	0.172	0.077	0.574	0.517	0.230
TBJA226*006C1#00++	A	22	6	3	1.32	13.2	6	0.075	0.156	0.142	0.063	0.474	0.427	0.190
TBJA226*006L1#00++	A	22	6	0.5	1.32	13.2	6	0.075	0.387	0.349	0.155	0.194	0.174	0.077
TBJB226*006C1#00++	B	22	6	2.5	1.32	13.2	6	0.085	0.184	0.166	0.074	0.461	0.415	0.184
TBJB226*006L1#00++	B	22	6	0.375	1.32	13.2	6	0.085	0.428	0.387	0.190	0.179	0.161	0.071
TBJC226*006C1#00++	C	22	6	2.2	1.32	13.2	6	0.110	0.224	0.201	0.089	0.492	0.443	0.197
TBJA336*006L1#00++	A	33	6	0.6	1.98	19.8	8	0.075	0.354	0.318	0.141	0.212	0.191	0.085
TBJB336*006C1#00++	B	33	6	2.2	1.98	19.8	6	0.085	0.197	0.177	0.079	0.432	0.389	0.173
TBJB336*006L1#00++	B	33	6	0.6	1.98	19.8	6	0.085	0.376	0.339	0.151	0.226	0.203	0.090
TBJA476*006L1#00++	A	47	6	0.8	2.82	28.2	6	0.075	0.306	0.276	0.122	0.245	0.220	0.098
TBJB476*006C1#00++	B	47	6	0.35	2.82	28.2	6	0.085	0.444	0.404	0.197	0.172	0.155	0.069
TBJB476*006L1#00++	B	47	6	0.25	2.82	28.2	6	0.085	0.533	0.525	0.233	0.146	0.131	0.058
TBJC476*006C1#00++	C	47	6	1.6	2.82	28.2	6	0.110	0.282	0.236	0.105	0.420	0.378	0.168
TBJC476*006L1#00++	C	47	6	0.1	2.82	28.2	6	0.110	0.606	0.545	0.242	0.182	0.163	0.073
TBJD476*006C1#00++	D	47	6	1.1	2.82	28.2	6	0.150	0.369	0.332	0.148	0.406	0.366	0.162
TBJB686*006C1#00++	B	68	6	1.8	4.08	40.8	8	0.085	0.217	0.196	0.087	0.391	0.352	0.156
TJB686*006C1#00++	B	68	6	0.25	4.08	40.8	8	0.085	0.583	0.525	0.233	0.146	0.131	0.058
TBJC686*006C1#00++	C	68	6	1.6	4.08	40.8	8	0.110	0.282	0.236	0.105	0.420	0.378	0.168
TBJC686*006L1#00++	C	68	6	0.15	4.08	40.8	6	0.110	0.856	0.771	0.343	0.128	0.116	0.051
TBJD686*006C1#00++	D	68	6	0.9	4.08	40.8	6	0.150	0.408	0.367	0.163	0.367	0.331	0.147
TBJD686*006L1#00++	D	68	6	0.4	4.08	40.8	6	0.150	0.461	0.415	0.184	0.184	0.166	0.074
TBJB107*006C1#00++	B	100	6	0.25	6	60	10	0.085	0.583	0.525	0.233	0.146	0.131	0.058
TBJC107*006C1#00++	C	100	6	0.9	6	60	10	0.110	0.350	0.315	0.140	0.315	0.283	0.126
TBJC107*006L1#00++	C	100	6	0.15	6	60	10	0.110	0.856	0.771	0.343	0.128	0.116	0.051
TBJD107*006C1#00++	D	100	6	0.9	6	60	10	0.150	0.408	0.367	0.163	0.367	0.331	0.147
TBJC157*006C1#00++	C	150	6	0.09	9	90	10	0.110	0.995	0.909	0.442	0.099	0.090	0.040
TBJC157*006L1#00++	C	150	6	0.05	9	90	10	0.110	1.483	1.335	0.593	0.074	0.067	0.030
TBJD157*006C1#00++	D	150	6	0.9	9	90	10	0.150	0.408	0.367	0.163	0.367	0.331	0.147
TBJD157*006L1#00++	D	150	6	0.05	9	90	10	0.150	1.732	1.559	0.693	0.087	0.078	0.035
TBJC227*006C1#00++	C	220	6	1.2	13.2	132	8	0.110	0.303	0.272	0.121	0.363	0.327	0.145
TBJC227*006L1#00++	C	220	6	0.07	13.2	132	8	0.110	1.254	1.128	0.501	0.088	0.079	0.035
TBJD227*006C1#00++	D	220	6	0.9	13.2	132	8	0.150	0.408	0.367	0.163	0.367	0.331	0.147
TBJD227*006L1#00++	D	220	6	0.1	13.2	132	8	0.150	1.225	1.102	0.490	0.122	0.110	0.049
TBJE227*006L1#00++	E	220	6	0.1	13.2	132	8	0.165	1.285	1.156	0.514	0.128	0.116	0.051
TBJD337*006C1#00++	D	330	6	0.045	19.8	198	8	0.150	1.326	1.225	0.593	0.087	0.078	0.035
TBJE337*006C1#00++	E	330	6	0.9	19.8	198	8	0.165	0.428	0.385	0.171	0.385	0.347	0.154
TBJE337*006L1#00++	E	330	6	0.1	19.8	198	8	0.165	1.285	1.156	0.514	0.128	0.116	0.051
TBJA337*006C1#00++	A	330	6	0.1	19.8	198	8	0.250	1.581	1.423	0.632	0.158	0.142	0.063
TBJD477*006C1#00++	D	470	6	0.06	28.2	282	12	0.150	1.581	1.423	0.632	0.095	0.085	0.038
TBJD477*006L1#00++	D	470	6	0.045	28.2	282	12	0.165	1.826	1.643	0.730	0.082	0.074	0.033
TBJE477*006C1#00++	E	470	6	0.9	28.2	282	12	0.165	0.428	0.385	0.171	0.385	0.347	0.154
TBJE477*006L1#00++	E	470	6	0.05	28.2	282	12	0.165	1.817	1.635	0.727	0.091	0.082	0.036
TBJA477*006C1#00++	A	470	6	0.1	28.2	282	12	0.250	1.581	1.423	0.632	0.158	0.142	0.063
TBJA477*006L1#00++	A	470	6	0.055	28.2	282	12	0.250	2.132	1.919	0.853	0.117	0.106	0.047
TBJE687*006C1#00++	E	680	6	0.06	40.8	408	10	0.165	1.658	1.492	0.663	0.099	0.090	0.040
TBJE687*006L1#00++	E	680	6	0.045	40.8	408	10	0.165	1.915	1.723	0.766	0.096	0.078	0.034
TBJA687*006C1#00++	A	680	6	0.04	40.8	408	10	0.250	2.500	2.250	1.000	0.100	0.090	0.040
TBJA687*006L1#00++	A	680	6	0.035	40.8	408	10	0.250	2.673	2.405	1.069	0.094	0.084	0.037

All technical data relates to an ambient temperature of +25°C. Capacitance and DF are measured at 120Hz, 0.5V RMS with a maximum DC bias of 2.2 volts. DCL is measured at rated voltage after 5 minutes.

NOTE: AVX reserves the right to supply a higher voltage rating or tighter tolerance part in the same case size, to the same reliability standards.



TBJ Series

COTS-Plus



RATING & PART NUMBER REFERENCE	Parametric Specifications by Rating per MIL-PRF-55365/4										Typical RMS Ripple Data by Rating						
	Cap @ 120Hz µF @ 25°C	DC Rated Voltage @ +85°C V	ESR @ 100kHz @ +25°C Ohms	DCL max		DF Max		Power Dissipation W	25°C Ripple Current (100kHz) A	85°C Ripple Current (100kHz) A	125°C Ripple Current (100kHz) A	25°C Ripple Voltage (100kHz) V	85°C Ripple Voltage (100kHz) V	125°C Ripple Voltage (100kHz) V			
				+25°C (µA)	+85°C (µA)	+25°C (%)	+85/+125°C (%)								+25°C (100kHz)	85°C (100kHz)	125°C (100kHz)
AVX COTS-Plus P/N Case																	
TB1A108'006GJ#00++	V 1000	6	0.05	60	600	1200	16	19	21	21	0.250	2.236	2.012	0.894	0.112	0.101	0.045
TB1A108'006LJ#00++	V 1000	6	0.04	60	600	1200	16	19	21	21	0.250	2.500	2.250	1.000	0.100	0.090	0.040
TB1A108'010CJ#00++	A 1	10	1.0	1	1.2	1.2	4	6	6	6	0.075	0.087	0.078	0.036	0.866	0.779	0.346
TB1A155'010CJ#00++	A 1.5	10	1.5	1.5	1.5	1.5	6	6	6	6	0.075	0.087	0.087	0.039	0.775	0.697	0.310
TB1A225'010CJ#00++	A 2.2	10	1.8	2.2	2.2	2.64	6	6	6	6	0.075	0.097	0.087	0.039	0.775	0.697	0.310
TB1A225'010LJ#00++	A 2.2	10	1.8	2.2	2.2	4.4	6	6	6	6	0.075	0.204	0.184	0.082	0.367	0.331	0.147
TB1B335'010CJ#00++	B 3.3	10	5.5	3.3	3.3	3.96	6	6	6	6	0.085	0.124	0.112	0.050	0.684	0.615	0.273
TB1A475'010CJ#00++	A 4.7	10	5	4.7	4.7	9.4	6	6	6	6	0.075	0.122	0.110	0.049	0.612	0.551	0.245
TB1A475'010LJ#00++	A 4.7	10	1.4	4.7	4.7	9.4	6	6	6	6	0.075	0.231	0.208	0.093	0.324	0.292	0.130
TB1B475'010CJ#00++	B 4.7	10	4.5	4.7	4.7	5.64	6	6	6	6	0.085	0.137	0.124	0.055	0.618	0.557	0.247
TB1A685'010CJ#00++	A 6.8	10	4	6.8	6.8	13.6	6	6	6	6	0.075	0.137	0.123	0.055	0.548	0.493	0.219
TB1A685'010LJ#00++	A 6.8	10	1.8	6.8	6.8	13.6	6	6	6	6	0.075	0.204	0.184	0.082	0.367	0.331	0.147
TB1B685'010CJ#00++	B 6.8	10	3.5	6.8	6.8	8.16	6	6	6	6	0.085	0.156	0.140	0.062	0.545	0.491	0.218
TB1A106'010CJ#00++	A 10	10	3	1	10	20	6	6	6	6	0.075	0.158	0.142	0.063	0.474	0.427	0.190
TB1A106'010LJ#00++	A 10	10	1.8	1	10	20	6	6	6	6	0.075	0.204	0.184	0.082	0.367	0.331	0.147
TB1B106'010CJ#00++	B 10	10	2.5	1	10	20	6	6	6	6	0.085	0.184	0.166	0.074	0.461	0.415	0.184
TB1A156'010CJ#00++	A 15	10	3.2	1.5	15	30	6	6	6	6	0.075	0.153	0.138	0.061	0.490	0.441	0.196
TB1A156'010LJ#00++	A 15	10	1	1.5	15	30	6	6	6	6	0.075	0.274	0.246	0.110	0.274	0.246	0.110
TB1B156'010CJ#00++	B 15	10	2.8	1.5	15	30	6	6	6	6	0.085	0.174	0.157	0.070	0.488	0.439	0.195
TB1B156'010LJ#00++	B 15	10	0.45	1.5	15	30	6	6	6	6	0.085	0.435	0.391	0.174	0.196	0.176	0.078
TB1C156'010CJ#00++	C 15	10	2.5	1.5	15	18	6	6	6	6	0.110	0.210	0.189	0.084	0.524	0.472	0.210
TB1B225'010CJ#00++	B 22	10	2.4	2.2	22	44	6	6	6	6	0.085	0.193	0.169	0.059	0.452	0.406	0.181
TB1B225'010LJ#00++	B 22	10	0.7	2.2	22	44	6	6	6	6	0.085	0.348	0.314	0.139	0.244	0.220	0.098
TB1C225'010CJ#00++	C 22	10	1	2.2	22	44	6	6	6	6	0.110	0.332	0.298	0.133	0.332	0.298	0.133
TB1C225'010LJ#00++	C 22	10	0.3	2.2	22	44	6	6	6	6	0.110	0.606	0.545	0.242	0.182	0.163	0.073
TB1A336'010CJ#00++	A 33	10	1.7	3.3	33	66	8	10	12	12	0.075	0.210	0.189	0.084	0.357	0.321	0.143
TB1A336'010LJ#00++	A 33	10	0.7	3.3	33	66	8	10	12	12	0.075	0.327	0.296	0.131	0.229	0.206	0.092
TB1B336'010CJ#00++	B 33	10	1.8	3.3	33	66	6	6	6	6	0.085	0.217	0.196	0.087	0.391	0.352	0.156
TB1B336'010LJ#00++	B 33	10	0.25	3.3	33	66	6	6	6	6	0.085	0.583	0.525	0.233	0.146	0.131	0.058
TB1C336'010CJ#00++	C 33	10	1.6	3.3	33	66	6	6	6	6	0.110	0.262	0.236	0.105	0.420	0.378	0.168
TB1C336'010LJ#00++	C 33	10	0.15	3.3	33	66	6	6	6	6	0.110	0.856	0.771	0.343	0.128	0.116	0.051
TB1D336'010CJ#00++	D 33	10	1.1	3.3	33	39.6	6	6	6	6	0.150	0.369	0.332	0.148	0.406	0.366	0.162
TB1B476'010CJ#00++	B 47	10	0.35	4.7	47	94	8	10	12	12	0.085	0.493	0.444	0.197	0.172	0.155	0.069
TB1B476'010LJ#00++	B 47	10	0.25	4.7	47	94	8	10	12	12	0.085	0.533	0.525	0.233	0.146	0.131	0.058
TB1C476'010CJ#00++	C 47	10	1.2	4.7	47	94	6	6	6	6	0.110	0.303	0.272	0.121	0.363	0.327	0.145
TB1C476'010LJ#00++	C 47	10	0.2	4.7	47	94	6	6	6	6	0.110	0.742	0.667	0.297	0.148	0.133	0.059
TB1D476'010CJ#00++	D 47	10	0.9	4.7	47	56.4	6	6	6	6	0.150	0.408	0.367	0.163	0.367	0.331	0.147
TB1D476'010LJ#00++	D 47	10	0.1	4.7	47	94	6	6	6	6	0.150	1.225	1.102	0.490	0.122	0.110	0.049
TB1B886'010CJ#00++	B 68	10	0.6	6.8	68	136	8	10	12	12	0.085	0.376	0.339	0.151	0.226	0.203	0.090
TB1C886'010CJ#00++	C 68	10	1.2	6.8	68	136	6	6	6	6	0.110	0.303	0.272	0.121	0.363	0.327	0.145
TB1D886'010CJ#00++	D 68	10	0.08	6.8	68	136	6	6	6	6	0.110	1.173	1.055	0.469	0.094	0.084	0.038
TB1D886'010LJ#00++	D 68	10	0.9	6.8	68	136	6	6	6	6	0.150	0.408	0.367	0.163	0.367	0.331	0.147
TB1B107'010CJ#00++	B 100	10	0.4	10	100	200	8	10	12	12	0.085	0.461	0.415	0.184	0.184	0.166	0.074
TB1C107'010CJ#00++	C 100	10	1.2	10	100	200	8	10	12	12	0.110	0.303	0.272	0.121	0.363	0.327	0.145
TB1C107'010LJ#00++	C 100	10	0.2	10	100	200	8	10	12	12	0.110	0.742	0.667	0.297	0.148	0.133	0.059
TB1D107'010CJ#00++	D 100	10	0.9	10	100	200	6	6	6	6	0.150	0.408	0.367	0.163	0.367	0.331	0.147
TB1D107'010LJ#00++	D 100	10	0.1	10	100	200	6	6	6	6	0.150	1.225	1.102	0.490	0.122	0.110	0.049
TB1E107'010CJ#00++	E 100	10	0.125	10	100	200	6	6	6	6	0.165	1.285	1.156	0.514	0.128	0.116	0.051
TB1D157'010CJ#00++	D 150	10	0.9	15	150	300	8	10	12	12	0.150	0.408	0.367	0.163	0.367	0.331	0.147
TB1D157'010LJ#00++	D 150	10	0.1	15	150	300	8	10	12	12	0.150	1.225	1.102	0.490	0.122	0.110	0.049
TB1E157'010CJ#00++	E 150	10	0.1	15	150	300	8	10	12	12	0.165	1.285	1.156	0.514	0.128	0.116	0.051
TB1D227'010CJ#00++	D 220	10	0.9	22	220	440	8	10	12	12	0.150	0.408	0.367	0.163	0.367	0.331	0.147
TB1D227'010LJ#00++	D 220	10	0.15	22	220	440	8	10	12	12	0.150	1.000	0.900	0.400	0.135	0.135	0.060
TB1E227'010CJ#00++	E 220	10	0.9	22	220	440	8	10	12	12	0.165	0.428	0.385	0.171	0.385	0.347	0.154
TB1E227'010LJ#00++	E 220	10	0.1	22	220	440	8	10	12	12	0.165	1.285	1.156	0.514	0.128	0.116	0.051

All technical data relates to an ambient temperature of +25°C. Capacitance and DF are measured at 120Hz, 0.5V RMS with a maximum DC bias of 2.2 volts. DCL is measured at rated voltage after 5 minutes.

NOTE: AVX reserves the right to supply a higher voltage rating or tighter tolerance part in the same case size, to the same reliability standards.

TBJ Series

COTS-Plus



RATING & PART NUMBER REFERENCE		Parametric Specifications by Rating per MIL-PRF-55365/4											Typical RMS Ripple Data by Rating					
		Cap @ 120Hz	DC Rated Voltage	ESR @ 100kHz	DF Max + (85/125)°C	DCL max +85°C	+125°C	+25°C	-55°C	Power Dissipation	25°C	85°C	125°C	25°C	85°C	125°C		
AVX COTS-Plus P/N	Case	µF @ +25°C	V @ +85°C	Ohms @ +25°C	(µA) @ +25°C	(µA) @ +125°C	(%) @ +25°C	(%) @ -55°C	W	A (100kHz)	A (100kHz)	A (100kHz)	A (100kHz)	V (100kHz)	V (100kHz)	V (100kHz)		
TBJD337010LL#00+0+	D	330	10	0.15	33	330	8	10	12	0.150	1.000	0.900	0.400	0.150	0.135	0.060		
TBJE337010CL#00+0+	E	330	10	0.9	33	330	8	10	12	0.165	0.428	0.385	0.171	0.385	0.347	0.154		
TBJE337010LL#00+0+	E	330	10	0.06	33	330	8	10	12	0.165	1.658	1.492	0.663	0.099	0.090	0.040		
TBJV337010CL#00+0+	V	330	10	0.1	33	330	8	10	12	0.250	1.581	1.423	0.632	0.158	0.142	0.063		
TBJV337010LL#00+0+	V	330	10	0.06	33	330	8	10	12	0.250	2.041	1.837	0.816	0.122	0.110	0.049		
TBJE477010CL#00+0+	E	470	10	0.9	47	470	8	10	12	0.165	0.428	0.385	0.171	0.385	0.347	0.154		
TBJE477010LL#00+0+	E	470	10	0.05	47	470	8	10	12	0.165	1.817	1.635	0.727	0.082	0.082	0.036		
TBJV477010CL#00+0+	V	470	10	0.1	47	470	8	10	12	0.250	1.581	1.423	0.632	0.158	0.142	0.063		
TBJV477010LL#00+0+	V	470	10	0.06	47	470	8	10	12	0.250	2.041	1.837	0.816	0.122	0.110	0.049		
TBJA6847015CL#00+0+	A	0.68	15	12	0.102	1.02	4	6	6	0.075	0.079	0.071	0.032	0.949	0.854	0.379		
TBJA1557015CL#00+0+	A	1	15	8	0.225	2.25	2.7	4	6	0.075	0.087	0.087	0.039	0.775	0.697	0.310		
TBJB2257015CL#00+0+	B	2.2	15	5.5	0.33	3.3	3.96	6	9	0.085	0.124	0.112	0.050	0.684	0.615	0.273		
TBJB3357015CL#00+0+	B	3.3	15	5	0.495	4.95	5.94	6	8	0.085	0.130	0.117	0.052	0.652	0.587	0.261		
TBJB4757015CL#00+0+	B	4.7	15	4	0.705	7.05	8.46	6	8	0.085	0.146	0.131	0.058	0.583	0.525	0.233		
TBJC1067015CL#00+0+	C	10	15	2.5	1.5	15	18	6	8	0.110	0.210	0.189	0.084	0.524	0.472	0.210		
TBJD2267015CL#00+0+	D	22	15	1.1	3.3	33	39.6	6	9	0.150	0.369	0.332	0.148	0.406	0.366	0.162		
TBJD3367015CL#00+0+	D	33	15	0.9	4.95	49.5	59.4	6	8	0.150	0.408	0.367	0.163	0.367	0.331	0.147		
TBJD157015LL#00+0+	D	150	15	0.05	5.625	56.25	112.5	6	9	0.150	1.792	1.599	0.693	0.087	0.078	0.035		
TBJA6847016CL#00+0+	A	0.68	16	12	0.109	1.088	2.176	4	6	0.075	0.079	0.071	0.032	0.949	0.854	0.379		
TBJA1057016CL#00+0+	A	1	16	8	0.16	1.6	3.2	4	6	0.075	0.087	0.078	0.035	0.866	0.779	0.346		
TBJA2257016CL#00+0+	A	2.2	16	5.5	0.352	3.52	7.04	6	9	0.075	0.117	0.105	0.047	0.642	0.578	0.257		
TBJA2257016LL#00+0+	A	2.2	16	1.8	0.352	3.52	7.04	6	10	0.075	0.204	0.184	0.082	0.367	0.331	0.147		
TBJB2257016CL#00+0+	B	2.2	16	5	0.352	3.52	7.04	6	8	0.085	0.130	0.117	0.052	0.652	0.587	0.261		
TBJA3357016CL#00+0+	A	3.3	16	5	0.528	5.28	10.56	6	9	0.075	0.122	0.110	0.049	0.612	0.551	0.245		
TBJA3357016LL#00+0+	A	3.3	16	3.5	0.528	5.28	10.56	6	9	0.075	0.146	0.132	0.059	0.512	0.461	0.205		
TBJB3357016CL#00+0+	B	3.3	16	4.5	0.528	5.28	10.56	6	10	0.085	0.137	0.124	0.055	0.548	0.493	0.219		
TBJA4757016CL#00+0+	A	4.7	16	4	0.752	7.52	15.04	6	9	0.075	0.137	0.123	0.055	0.548	0.493	0.219		
TBJA4757016LL#00+0+	A	4.7	16	2	0.752	7.52	15.04	6	10	0.075	0.194	0.174	0.077	0.387	0.349	0.155		
TBJB4757016CL#00+0+	B	4.7	16	3.1	0.752	7.52	15.04	6	8	0.085	0.166	0.149	0.066	0.513	0.462	0.205		
TBJB4757016LL#00+0+	B	4.7	16	0.8	0.752	7.52	15.04	6	10	0.085	0.326	0.293	0.130	0.261	0.235	0.104		
TBJA6857016CL#00+0+	A	6.8	16	2.5	1.088	10.88	21.76	6	9	0.075	0.173	0.156	0.089	0.433	0.390	0.173		
TBJA6857016LL#00+0+	A	6.8	16	1.5	1.088	10.88	21.76	6	10	0.075	0.224	0.201	0.089	0.302	0.302	0.134		
TBJB6857016CL#00+0+	B	6.8	16	2.5	1.088	10.88	21.76	6	8	0.085	0.184	0.166	0.074	0.461	0.415	0.184		
TBJB6857016LL#00+0+	B	6.8	16	0.6	1.088	10.88	21.76	6	9	0.085	0.376	0.339	0.151	0.226	0.203	0.090		
TBJA1057016LL#00+0+	A	10	16	3	1.6	16	32	6	10	0.075	0.158	0.142	0.063	0.474	0.427	0.190		
TBJA1057016CL#00+0+	A	10	16	2.8	1.6	16	32	6	10	0.075	0.274	0.246	0.110	0.274	0.246	0.110		
TBJB1067016CL#00+0+	B	10	16	2.8	1.6	16	32	6	9	0.085	0.174	0.157	0.070	0.488	0.439	0.195		
TBJB1067016LL#00+0+	B	10	16	0.5	1.6	16	32	6	9	0.085	0.412	0.371	0.165	0.206	0.186	0.082		
TBJC1067016CL#00+0+	C	10	16	2.5	1.6	16	32	6	8	0.110	0.210	0.189	0.084	0.524	0.472	0.210		
TBJC1067016LL#00+0+	C	10	16	0.5	1.6	16	32	6	9	0.110	0.469	0.422	0.188	0.235	0.211	0.094		
TBJB1567016CL#00+0+	B	15	16	0.8	2.4	24	48	6	6	0.085	0.326	0.293	0.130	0.261	0.235	0.104		
TBJC1567016CL#00+0+	C	15	16	1.8	2.4	24	48	6	9	0.110	0.247	0.222	0.099	0.445	0.400	0.178		
TBJB2267016CL#00+0+	B	22	16	2.3	3.52	35.2	70.4	6	6	0.085	0.192	0.173	0.077	0.442	0.398	0.177		
TBJB2267016LL#00+0+	B	22	16	0.6	3.52	35.2	70.4	6	9	0.085	0.376	0.339	0.151	0.226	0.203	0.090		
TBJC2267016CL#00+0+	C	22	16	1.6	3.52	35.2	70.4	6	8	0.110	0.282	0.262	0.105	0.420	0.378	0.168		
TBJC2267016LL#00+0+	C	22	16	0.375	3.52	35.2	70.4	6	9	0.110	0.542	0.487	0.217	0.203	0.183	0.081		
TBJD2267016CL#00+0+	D	22	16	1.1	3.52	35.2	70.4	6	8	0.150	0.369	0.332	0.148	0.406	0.366	0.162		
TBJB3367016CL#00+0+	B	33	16	0.35	5.28	52.8	105.6	6	10	0.085	0.443	0.404	0.197	0.172	0.155	0.069		
TBJC3367016CL#00+0+	C	33	16	1.5	5.28	52.8	105.6	6	9	0.110	0.271	0.244	0.108	0.406	0.366	0.162		
TBJC3367016LL#00+0+	C	33	16	0.3	5.28	52.8	105.6	6	9	0.110	0.606	0.545	0.242	0.182	0.163	0.073		
TBJD3367016CL#00+0+	D	33	16	0.9	5.28	52.8	105.6	6	10	0.150	0.408	0.367	0.163	0.367	0.331	0.147		
TBJD3367016LL#00+0+	D	33	16	0.2	5.28	52.8	105.6	6	9	0.150	0.866	0.779	0.346	0.173	0.156	0.069		
TBJC4767016CL#00+0+	C	47	16	1.5	7.52	75.2	150.4	6	6	0.110	0.271	0.244	0.108	0.406	0.366	0.162		
TBJC4767016LL#00+0+	C	47	16	0.35	7.52	75.2	150.4	6	9	0.110	0.561	0.505	0.224	0.196	0.177	0.078		
TBJD4767016CL#00+0+	D	47	16	0.9	7.52	75.2	150.4	6	10	0.150	0.408	0.367	0.163	0.367	0.331	0.147		
TBJD4767016LL#00+0+	D	47	16	0.15	7.52	75.2	150.4	6	9	0.150	1.000	0.900	0.400	0.150	0.135	0.060		

All technical data relates to an ambient temperature of +25°C. Capacitance and DF are measured at 120Hz, 0.5V RMS with a maximum DC bias of 2.2 volts. DCL is measured at rated voltage after 5 minutes. NOTE: AVX reserves the right to supply a higher voltage rating or tighter tolerance part in the same case size, to the same reliability standards.



RATING & PART NUMBER REFERENCE	Parametric Specifications by Rating per MIL-PRF-55365/4										Typical RMS Ripple Data by Rating									
	Cap @ 120Hz	DC Rated Voltage @ +85°C	ESR @ 100kHz	DCL max		DF Max		Power Dissipation	25°C		85°C		125°C		25°C		85°C		125°C	
				+25°C	+85°C	+25°C	+85/125°C		+25°C	+85°C	Ripple Current	Ripple Voltage	Ripple Current	Ripple Voltage	Ripple Current	Ripple Voltage	Ripple Current	Ripple Voltage	Ripple Current	Ripple Voltage
AVX COTS-Plus P/N Case	µF @ 25°C	V @ +85°C	Ohms @ +25°C	µA	µA	(%)	(%)	W	A (100kHz)	V (100kHz)	A (100kHz)	V (100kHz)	A (100kHz)	V (100kHz)	A (100kHz)	V (100kHz)	A (100kHz)	V (100kHz)	A (100kHz)	V (100kHz)
TBJC885*016CJL#00V++	C	68	16	0.2	10.88	108.8	217.6	6	9	10	0.110	0.148	0.133	0.059						
TBJC886*016LJL#00V++	C	68	16	0.125	10.88	108.8	217.6	6	9	10	0.110	0.117	0.106	0.047						
TBJD886*016CJL#00V++	D	68	16	0.9	10.88	108.8	217.6	6	9	10	0.150	0.367	0.331	0.147						
TBJD886*016LJL#00V++	D	68	16	0.07	10.88	108.8	217.6	6	9	10	0.150	0.102	0.092	0.041						
TBJD107*016CJL#00V++	D	100	16	0.9	16	160	320	6	9	10	0.150	0.367	0.331	0.147						
TBJD107*016LJL#00V++	D	100	16	0.125	16	160	320	6	9	10	0.150	0.137	0.123	0.055						
TBJE107*016CJL#00V++	E	100	16	0.9	16	160	320	6	9	10	0.165	0.347	0.316	0.144						
TBJE107*016LJL#00V++	E	100	16	0.1	16	160	320	6	9	10	0.165	0.128	0.116	0.051						
TBJD157*016CJL#00V++	D	150	16	0.9	24	240	480	6	9	10	0.150	0.367	0.331	0.147						
TBJD157*016LJL#00V++	D	150	16	0.15	24	240	480	6	9	10	0.150	0.135	0.123	0.051						
TBJE157*016CJL#00V++	E	150	16	0.3	24	240	480	6	9	10	0.165	0.222	0.200	0.089						
TBJE157*016LJL#00V++	E	150	16	0.1	24	240	480	6	9	10	0.165	0.128	0.116	0.051						
TBM157*016CJL#00V++	V	150	16	0.075	24	240	480	6	10	12	0.250	0.730	0.673	0.296						
TBM157*016LJL#00V++	V	150	16	0.045	24	240	480	6	8	10	0.250	0.106	0.095	0.042						
TBM227*016CJL#00V++	E	220	16	0.15	35.2	352	704	10	12	14	0.165	0.420	0.387	0.163						
TBM227*016LJL#00V++	E	220	16	0.1	35.2	352	704	10	12	14	0.165	0.128	0.116	0.051						
TBM474*020CJL#00V++	A	0.47	20	14	0.5	10	4	6	10	12	0.250	0.730	0.673	0.296						
TBA684*020CJL#00V++	A	0.68	20	12	0.136	1.36	1.632	4	6	6	0.075	0.079	0.071	0.032						
TBA105*020CJL#00V++	A	1	20	10	0.2	2	2.4	4	4	4	0.075	0.087	0.078	0.035						
TBA105*020LJL#00V++	A	1	20	3	0.2	2	4	4	4	6	0.075	0.158	0.142	0.063						
TBA155*020CJL#00V++	A	1.5	20	6.5	0.3	3	6	4	4	8	0.075	0.107	0.097	0.043						
TBA155*020LJL#00V++	B	1.5	20	6	0.3	3	3.6	6	6	8	0.085	0.119	0.107	0.043						
TBA225*020CJL#00V++	A	2.2	20	5.3	0.44	4.4	8.8	6	6	8	0.075	0.158	0.142	0.063						
TBA225*020LJL#00V++	A	2.2	20	3	0.44	4.4	8.8	6	6	9	0.075	0.158	0.142	0.063						
TBA225*020CJL#00V++	B	2.2	20	5	0.44	4.4	5.28	6	6	9	0.085	0.130	0.117	0.052						
TBA335*020LJL#00V++	A	3.3	20	2.5	0.66	6.6	13.2	6	6	9	0.075	0.173	0.156	0.069						
TBA335*020CJL#00V++	B	3.3	20	4	0.66	6.6	7.92	6	6	9	0.085	0.146	0.131	0.058						
TBA335*020LJL#00V++	B	3.3	20	1.3	0.66	6.6	13.2	6	6	8	0.085	0.256	0.230	0.102						
TBA475*020CJL#00V++	A	4.7	20	4	0.94	9.4	18.8	6	6	8	0.075	0.137	0.123	0.055						
TBA475*020LJL#00V++	A	4.7	20	1.8	0.94	9.4	18.8	6	6	8	0.075	0.204	0.184	0.082						
TBA75*020CJL#00V++	B	4.7	20	3	0.94	9.4	18.8	6	6	8	0.085	0.168	0.151	0.067						
TBA75*020LJL#00V++	B	4.7	20	0.75	0.94	9.4	18.8	6	6	10	0.085	0.337	0.303	0.135						
TBC475*020CJL#00V++	C	4.7	20	3	0.94	9.4	11.28	6	6	8	0.110	0.191	0.172	0.077						
TBA685*020LJL#00V++	A	6.8	20	1	1.36	13.6	27.2	6	6	8	0.075	0.274	0.246	0.110						
TBA685*020CJL#00V++	B	6.8	20	2.5	1.36	13.6	27.2	6	6	8	0.085	0.184	0.166	0.074						
TBA685*020LJL#00V++	B	6.8	20	0.6	1.36	13.6	27.2	6	6	9	0.085	0.376	0.339	0.151						
TBA685*020CJL#00V++	C	6.8	20	2.4	1.36	13.6	16.32	6	6	9	0.110	0.214	0.193	0.086						
TBA106*020LJL#00V++	B	10	20	1	2	20	40	6	6	8	0.085	0.201	0.181	0.080						
TBA106*020CJL#00V++	B	10	20	1.9	2	20	40	6	6	8	0.085	0.292	0.262	0.117						
TBA106*020LJL#00V++	C	10	20	0.5	2	20	40	6	6	9	0.110	0.241	0.217	0.096						
TBA106*020CJL#00V++	C	10	20	2	2	20	40	6	6	9	0.110	0.469	0.422	0.188						
TBA156*020CJL#00V++	B	15	20	3	30	30	60	6	6	8	0.085	0.206	0.186	0.082						
TBA156*020LJL#00V++	B	15	20	0.5	3	30	60	6	6	8	0.085	0.412	0.371	0.165						
TBC156*020CJL#00V++	C	15	20	1.7	3	30	60	6	6	8	0.110	0.254	0.229	0.102						
TBC156*020LJL#00V++	C	15	20	0.4	3	30	60	6	6	8	0.110	0.524	0.472	0.210						
TBD156*020CJL#00V++	D	15	20	1.1	3	30	36	6	6	8	0.150	0.369	0.332	0.148						
TBD225*020CJL#00V++	B	22	20	0.6	4.4	44	88	6	6	9	0.085	0.376	0.339	0.151						
TBD225*020LJL#00V++	B	22	20	0.4	4.4	44	88	6	6	8	0.085	0.461	0.415	0.184						
TBC225*020CJL#00V++	C	22	20	1.6	4.4	44	88	6	6	8	0.110	0.236	0.203	0.090						
TBC225*020LJL#00V++	C	22	20	0.15	4.4	44	88	6	6	8	0.110	0.856	0.771	0.343						
TBD225*020CJL#00V++	D	22	20	0.9	4.4	44	52.8	6	6	9	0.150	0.408	0.367	0.166						
TBD225*020LJL#00V++	D	22	20	0.2	4.4	44	88	6	6	9	0.150	0.866	0.779	0.346						
TBC335*020CJL#00V++	C	33	20	1.5	6.6	66	132	6	6	8	0.110	0.271	0.244	0.108						

All technical data relates to an ambient temperature of +25°C. Capacitance and DF are measured at 120Hz, 0.5V RMS with a maximum DC bias of 2.2 volts. DCL is measured at rated voltage after 5 minutes.

NOTE: AVX reserves the right to supply a higher voltage rating or tighter tolerance part in the same case size, to the same reliability standards.

RATING & PART NUMBER REFERENCE		Parametric Specifications by Rating per MIL-PRF-55365/4										Typical RMS Ripple Data by Rating									
		Cap @ 120Hz	DC Rated Voltage	ESR @ 100kHz	DCL max	+25°C	+85°C	+125°C	+25°C	-55°C	DF Max	Power Dissipation	25°C	85°C	125°C	25°C	85°C	125°C			
AVX COTS-Plus P/N	Case	µF @ +25°C	V @ +85°C	Ohms	(µA)	(µA)	(%)	(%)	(%)	(%)	W	A (100kHz)	A (100kHz)	A (100kHz)	V (100kHz)	V (100kHz)	V (100kHz)				
TBJC226*025L1#00++	C	22	25	0.275	5.5	110	6	8	10	10	0.110	0.632	0.569	0.253	0.174	0.157	0.070				
TBJD226*025C1#00++	D	22	25	0.9	5.5	110	6	8	10	10	0.150	0.408	0.367	0.163	0.367	0.331	0.147				
TBJD226*025L1#00++	D	22	25	0.2	5.5	55	6	8	10	10	0.150	0.866	0.779	0.346	0.173	0.156	0.069				
TBJD336*025C1#00++	D	33	25	0.9	8.25	165	6	8	10	10	0.150	0.408	0.367	0.163	0.367	0.331	0.147				
TBJD336*025L1#00++	D	33	25	0.1	8.25	82.5	6	8	10	10	0.150	1.225	1.102	0.490	0.122	0.110	0.049				
TBJE336*025C1#00++	E	33	25	0.9	8.25	82.5	6	8	10	10	0.165	0.428	0.385	0.171	0.385	0.347	0.154				
TBJE336*025L1#00++	E	33	25	0.3	8.25	82.5	6	8	10	10	0.165	0.742	0.667	0.297	0.222	0.200	0.089				
TBJD476*025C1#00++	D	47	25	0.9	11.75	117.5	6	8	10	10	0.150	0.408	0.367	0.163	0.367	0.331	0.147				
TBJD476*025L1#00++	D	47	25	0.25	11.75	117.5	6	8	10	10	0.150	0.775	0.697	0.310	0.194	0.174	0.077				
TBJE476*025C1#00++	E	47	25	0.1	11.75	117.5	6	8	10	10	0.165	1.285	1.156	0.514	0.128	0.116	0.051				
TBJE476*025L1#00++	E	47	25	0.08	11.75	117.5	6	8	10	10	0.165	1.436	1.293	0.574	0.115	0.103	0.046				
TBJE666*025C1#00++	E	66	25	0.2	17	170	6	8	10	10	0.165	0.908	0.817	0.363	0.182	0.169	0.073				
TBJE666*025L1#00++	E	66	25	0.125	17	170	6	8	10	10	0.165	1.149	1.034	0.460	0.144	0.129	0.057				
TBJV666*025L1#00++	V	66	25	0.095	17	170	6	8	10	10	0.250	1.622	1.460	0.649	0.154	0.139	0.062				
TBJV107*025L1#00++	V	100	25	0.1	25	250	8	10	12	10	0.250	1.581	1.423	0.632	0.158	0.142	0.063				
TBJA104*035C1#00++	A	0.1	35	24	0.035	0.35	0.42	4	6	6	0.075	0.056	0.050	0.022	1.342	1.207	0.537				
TBJA154*035C1#00++	A	0.15	35	21	0.5	5	10	4	6	6	0.075	0.060	0.054	0.024	1.255	1.129	0.502				
TBJA224*035C1#00++	A	0.22	35	18	0.5	5	10	4	6	6	0.075	0.065	0.058	0.026	1.162	1.046	0.465				
TBJA224*035L1#00++	A	0.22	35	6	0.077	0.77	1.54	4	6	6	0.075	0.112	0.101	0.045	0.671	0.604	0.268				
TBJA334*035C1#00++	A	0.33	35	15	0.5	5	10	4	6	6	0.075	0.071	0.064	0.028	1.061	0.955	0.424				
TBJA334*035L1#00++	A	0.33	35	6	0.116	1.165	2.31	4	6	6	0.075	0.112	0.101	0.045	0.671	0.604	0.268				
TBJA474*035C1#00++	A	0.47	35	12	1.645	3.29	4	6	8	8	0.075	0.079	0.071	0.032	0.949	0.854	0.379				
TBJA474*035L1#00++	A	0.47	35	6	0.165	1.645	3.29	4	6	6	0.075	0.112	0.101	0.045	0.671	0.604	0.268				
TBJB474*035C1#00++	B	0.47	35	10	0.165	1.645	1.974	4	6	6	0.085	0.092	0.083	0.037	0.922	0.830	0.369				
TBJB474*035L1#00++	B	0.47	35	4	0.165	1.645	3.29	4	6	6	0.085	0.146	0.131	0.052	0.583	0.525	0.233				
TBJA684*035C1#00++	A	0.68	35	8	0.238	2.38	4.76	4	6	6	0.075	0.097	0.087	0.039	0.775	0.697	0.310				
TBJA684*035L1#00++	A	0.68	35	6	0.238	2.38	4.76	4	6	6	0.075	0.112	0.101	0.045	0.671	0.604	0.268				
TBJB684*035C1#00++	B	0.68	35	8	0.238	2.38	2.856	4	6	6	0.085	0.103	0.093	0.041	0.825	0.742	0.330				
TBJA105*035C1#00++	A	1	35	7.5	3.5	3.5	7	4	6	6	0.075	0.100	0.090	0.040	0.750	0.675	0.300				
TBJA105*035L1#00++	A	1	35	3	3.5	3.5	7	4	6	6	0.075	0.158	0.142	0.063	0.474	0.427	0.190				
TBJB105*035C1#00++	B	1	35	6.5	3.5	3.5	4.2	4	6	6	0.085	0.114	0.103	0.046	0.743	0.669	0.297				
TBJB105*035L1#00++	B	1	35	2	3.5	3.5	7	4	6	6	0.085	0.206	0.186	0.082	0.412	0.371	0.165				
TBJA155*035C1#00++	A	1.5	35	7.5	5.25	5.25	10.5	6	8	8	0.075	0.100	0.090	0.040	0.750	0.675	0.300				
TBJA155*035L1#00++	A	1.5	35	5.2	5.25	5.25	10.5	6	8	8	0.085	0.128	0.115	0.051	0.665	0.598	0.266				
TBJB155*035C1#00++	B	1.5	35	2.5	5.25	5.25	10.5	6	8	8	0.085	0.184	0.166	0.074	0.461	0.415	0.184				
TBJB155*035L1#00++	B	1.5	35	4.5	5.25	5.25	6.3	6	8	8	0.110	0.156	0.141	0.063	0.704	0.633	0.281				
TBJA225*035C1#00++	A	2.2	35	4.5	0.77	7.7	15.4	6	8	8	0.075	0.129	0.116	0.052	0.581	0.523	0.232				
TBJA225*035L1#00++	A	2.2	35	1.5	0.77	7.7	15.4	6	8	8	0.075	0.224	0.201	0.089	0.335	0.302	0.134				
TBJB225*035C1#00++	B	2.2	35	4.2	0.77	7.7	15.4	6	8	8	0.085	0.142	0.128	0.057	0.597	0.538	0.239				
TBJB225*035L1#00++	B	2.2	35	2	0.77	7.7	15.4	6	8	8	0.085	0.206	0.186	0.082	0.412	0.371	0.165				
TBJC225*035C1#00++	C	2.2	35	3.5	0.77	7.7	9.24	6	8	8	0.110	0.177	0.160	0.071	0.620	0.558	0.248				
TBJC225*035L1#00++	C	2.2	35	1	0.77	7.7	15.4	6	8	8	0.110	0.332	0.298	0.133	0.332	0.298	0.133				
TBJB335*035C1#00++	B	3.3	35	3.5	1.155	11.55	23.1	6	8	8	0.085	0.156	0.140	0.062	0.545	0.491	0.218				
TBJB335*035L1#00++	B	3.3	35	1	1.155	11.55	23.1	6	8	8	0.085	0.292	0.262	0.117	0.292	0.262	0.117				
TBJC335*035C1#00++	C	3.3	35	2.5	1.155	11.55	13.86	6	8	8	0.110	0.210	0.189	0.084	0.524	0.472	0.210				
TBJC335*035L1#00++	C	3.3	35	0.7	1.155	11.55	23.1	6	8	8	0.110	0.336	0.307	0.159	0.277	0.250	0.111				
TBJB475*035C1#00++	B	4.7	35	3.1	1.645	16.45	32.9	6	8	8	0.085	0.166	0.149	0.066	0.513	0.462	0.205				
TBJB475*035L1#00++	B	4.7	35	0.7	1.645	16.45	32.9	6	8	8	0.085	0.314	0.284	0.139	0.244	0.220	0.098				
TBJC475*035C1#00++	C	4.7	35	2.2	1.645	16.45	32.9	6	8	8	0.110	0.224	0.201	0.089	0.492	0.443	0.197				
TBJC475*035L1#00++	C	4.7	35	0.6	1.645	16.45	32.9	6	8	8	0.110	0.428	0.385	0.171	0.257	0.231	0.103				
TBJD475*035C1#00++	D	4.7	35	1.5	1.645	16.45	19.74	6	8	8	0.150	0.316	0.285	0.126	0.474	0.427	0.190				
TBJD475*035L1#00++	D	4.7	35	0.5	1.645	16.45	32.9	6	8	8	0.150	0.548	0.493	0.219	0.274	0.246	0.110				
TBJC685*035C1#00++	C	6.8	35	1.8	2.38	23.8	47.6	6	8	8	0.110	0.247	0.222	0.099	0.445	0.400	0.178				
TBJC685*035L1#00++	C	6.8	35	0.35	2.38	23.8	47.6	6	8	8	0.110	0.561	0.505	0.224	0.196	0.177	0.078				

All technical data relates to an ambient temperature of +25°C. Capacitance and DF are measured at 120Hz. 0.5V RMS with a maximum DC bias of 2.2 volts. DCL is measured at rated voltage after 5 minutes. NOTE: AVX reserves the right to supply a higher voltage rating or tighter tolerance part in the same case size, to the same reliability standards.

TBJ Series

COTS-Plus



RATING & PART NUMBER REFERENCE	Parametric Specifications by Rating per MIL-PRF-55365/4				Typical RMS Ripple Data by Rating							
	Cap @ 120Hz	DC Rated Voltage	ESR @ 100kHz	DCL max	+25°C	+85°C	+125°C	+25°C	85°C	125°C	125°C	
	µF @ 25°C	@ +85°C V	Ohms @ +25°C	(µA)	(µA)	(µA)	(µA)	Ripple Current (100kHz)	Ripple Current (100kHz)	Ripple Current (100kHz)	Ripple Voltage (100kHz)	Ripple Voltage (100kHz)
AVX COTS-Plus P/N Case												
TBJD885035CL#000++	6.8	35	1.3	2.38	23.8	28.56	6	9	0.150	0.340	0.306	0.442
TBJD885035LL#000++	6.8	35	0.5	2.38	23.8	47.6	6	9	0.150	0.548	0.493	0.274
TBJC1050350CL#000++	10	35	1.6	3.5	35	70	6	9	0.110	0.262	0.236	0.420
TBJC105035LL#000++	10	35	0.6	3.5	35	70	6	9	0.110	0.428	0.385	0.257
TBJD1050350CL#000++	10	35	1	3.5	35	70	6	9	0.150	0.387	0.349	0.387
TBJD105035LL#000++	10	35	0.3	3.5	35	70	6	9	0.150	0.707	0.636	0.212
TBJE1050350CL#000++	10	35	0.25	3.5	35	70	6	10	0.165	0.812	0.731	0.325
TBJE105035LL#000++	10	35	0.2	3.5	35	70	6	10	0.165	0.908	0.817	0.182
TBJC1550350CL#000++	15	35	1.4	5.25	52.5	105	6	9	0.110	0.290	0.252	0.392
TBJC155035LL#000++	15	35	0.35	5.25	52.5	105	6	10	0.110	0.561	0.505	0.196
TBJD1550350CL#000++	15	35	0.9	5.25	52.5	105	6	9	0.150	0.408	0.367	0.367
TBJD155035LL#000++	15	35	0.3	5.25	52.5	105	6	9	0.150	0.707	0.636	0.212
TBD12250350CL#000++	22	35	0.9	7.7	77	154	6	9	0.150	0.408	0.367	0.367
TBD1225035LL#000++	22	35	0.4	7.7	77	154	6	9	0.150	0.612	0.551	0.245
TBE2250350CL#000++	22	35	0.9	7.7	77	154	6	9	0.165	0.428	0.385	0.347
TBE225035LL#000++	22	35	0.3	7.7	77	154	6	9	0.165	0.742	0.667	0.292
TBD3350350CL#000++	33	35	0.9	11.55	115.5	231	6	9	0.150	0.408	0.367	0.367
TBD335035LL#000++	33	35	0.3	11.55	115.5	231	6	9	0.150	0.707	0.636	0.212
TBE3350350CL#000++	33	35	0.25	11.55	115.5	231	6	10	0.165	0.812	0.731	0.325
TBE335035LL#000++	33	35	0.1	11.55	115.5	231	6	10	0.165	1.285	1.156	0.514
TBVA360350CL#000++	36	35	0.2	11.55	115.5	231	6	10	0.250	1.118	1.006	0.447
TBVA36035LL#000++	36	35	0.25	16.45	164.5	329	6	10	0.165	0.812	0.731	0.325
TBE4750350CL#000++	47	35	0.2	16.45	164.5	329	6	9	0.165	0.908	0.817	0.182
TBE475035LL#000++	47	35	0.4	16.45	164.5	329	6	10	0.165	1.645	1.493	0.576
TBVA750350CL#000++	47	35	0.2	16.45	164.5	329	6	10	0.250	1.118	1.006	0.447
TBVA75035LL#000++	47	35	0.2	16.45	164.5	329	6	10	0.250	1.118	1.006	0.447
TBVA6850350CL#000++	68	35	0.2	23.8	238	476	6	9	0.250	1.118	1.006	0.447
TBVA685035LL#000++	68	35	0.15	23.8	238	476	6	10	0.250	1.291	1.162	0.516
TBA1040500CL#000++	0.1	50	22	0.05	0.5	0.6	6	8	0.075	0.053	0.053	0.203
TBA1540500CL#000++	0.15	50	21	0.02	0.2	0.4	4	6	0.075	0.080	0.084	0.024
TBA154050LL#000++	0.15	50	9	0.075	0.75	1.5	4	6	0.085	0.091	0.092	0.822
TBA154050CL#000++	0.15	50	17	0.075	0.75	0.9	4	6	0.085	0.071	0.064	0.028
TBA2240500CL#000++	0.22	50	18	0.11	1.1	2.2	4	6	0.075	0.065	0.058	0.026
TBA224050LL#000++	0.22	50	7	0.11	1.1	2.2	4	6	0.075	0.104	0.093	0.041
TBA224050CL#000++	0.22	50	14	0.11	1.1	1.32	4	6	0.085	0.078	0.070	0.031
TB12340500CL#000++	0.33	50	12	0.165	1.65	1.98	4	6	0.085	0.084	0.076	0.034
TB1234050CL#000++	0.47	50	8	0.235	2.35	2.82	4	6	0.110	0.117	0.106	0.047
TBA6840500CL#000++	0.68	50	7.9	0.34	3.4	6.8	4	6	0.075	0.097	0.088	0.039
TB1234050CL#000++	0.68	50	7	0.34	3.4	4.08	4	6	0.110	0.125	0.113	0.050
TB1050500CL#000++	1	50	6	0.5	5	6	4	6	0.110	0.135	0.122	0.054
TB105050LL#000++	1	50	2.5	0.5	5	10	4	6	0.110	0.210	0.199	0.084
TB105050CL#000++	1.5	50	5	0.75	7.5	15	6	8	0.110	0.148	0.133	0.059
TB1550500CL#000++	1.5	50	1.5	0.75	7.5	15	6	10	0.110	0.271	0.244	0.108
TB155050CL#000++	1.5	50	4	0.75	7.5	9	6	8	0.150	0.194	0.174	0.077
TBD2250500CL#000++	2.2	50	2.5	1.1	11	13.2	6	8	0.150	0.245	0.220	0.098
TBD225050LL#000++	2.2	50	1.2	1.1	11	22	6	10	0.150	0.354	0.318	0.141
TBD225050CL#000++	3.3	50	2	1.65	16.5	19.8	6	9	0.150	0.274	0.246	0.110
TBD3350500CL#000++	3.3	50	0.8	1.65	16.5	33	6	10	0.150	0.433	0.390	0.173
TBD4750500CL#000++	4.7	50	1.5	2.35	23.5	28.2	6	9	0.150	0.316	0.285	0.126
TBD475050CL#000++	4.7	50	0.3	2.35	23.5	47	6	9	0.150	0.707	0.636	0.283
TBD8850500CL#000++	6.8	50	1	3.4	34	68	6	9	0.150	0.387	0.349	0.155
TBD885050LL#000++	6.8	50	0.5	3.4	34	68	6	9	0.150	0.548	0.493	0.246
TBE1050500CL#000++	10	50	0.5	5	50	100	6	10	0.165	0.574	0.517	0.230
TBE105050LL#000++	10	50	0.4	5	50	100	6	10	0.165	0.642	0.578	0.257

All technical data relates to an ambient temperature of +25°C. Capacitance and DF are measured at 120Hz, 0.5V RMS with a maximum DC bias of 2.2 volts. DCL is measured at rated voltage after 5 minutes.

NOTE: AVX reserves the right to supply a higher voltage rating or tighter tolerance part in the same case size, to the same reliability standards.



RATING & PART NUMBER REFERENCE	Parametric Specifications by Rating per MIL-PRF-55365/4				Typical RMS Ripple Data by Rating										
	Cap @ 120Hz @ 25°C	DC Rated Voltage @ +85°C	ESR @ 100kHz @ +25°C	DCL max +85°C	+25°C (µA)	+125°C (µA)	+25°C (%)	DF Max + (85/125)°C (%)	-55°C (%)	Power Dissipation W	25°C Ripple Current (100kHz) A	85°C Ripple Current (100kHz) A	125°C Ripple Current (100kHz) A	25°C Ripple Voltage (100kHz) V	85°C Ripple Voltage (100kHz) V
AVX COTS-Plus P/N Case	µF @ 25°C	V @ +85°C	Ohms @ +25°C	(µA) @ +85°C	(µA) @ +125°C	(%) @ +25°C	(%) @ + (85/125)°C	(%) @ -55°C	W	A @ (100kHz) 25°C	A @ (100kHz) 85°C	A @ (100kHz) 125°C	V @ (100kHz) 25°C	V @ (100kHz) 85°C	V @ (100kHz) 125°C
TBM106*050C1#00^++	10	50	0.65	5	100	3			0.250	0.620	0.558	0.248	0.403	0.363	0.161
TBJD156*050C1#00^++	15	50	0.6	7.5	150	4	6	6	0.150	0.500	0.450	0.200	0.300	0.270	0.120
TBJE156*050C1#00^++	15	50	0.6	7.5	150	8	10	12	0.165	0.524	0.472	0.210	0.315	0.283	0.126
TBJE156*050L1#00^++	15	50	0.25	7.5	150	6	9	10	0.165	0.812	0.731	0.325	0.203	0.183	0.081
TBM226*050C1#00^++	22	50	0.6	11	220	8	10	12	0.250	0.645	0.581	0.258	0.387	0.349	0.155
TBM226*050L1#00^++	22	50	0.39	11	220	8	10	12	0.250	0.801	0.721	0.320	0.312	0.281	0.125

All technical data relates to an ambient temperature of +25°C. Capacitance and DF are measured at 120Hz, 0.5V RMS with a maximum DC bias of 2.2 volts. DCL is measured at rated voltage after 5 minutes. **NOTE: AVX reserves the right to supply a higher voltage rating or tighter tolerance part in the same case size, to the same reliability standards.**